

COMMUNICATION & CONTROL CABLES



Commercial Applications 300V CMR/ CMG FT4 Rated



RoHS Compliant

Cables are manufactured to meet current NEC guidelines and are verified by outside standards organizations including UL and ETL.

Product Description	Specifications	Applications	Color Code Chart		
Bare copper conductors, PVC insulation, short overall twist lengths, Filler as required, Shielded tape with drain wire, Gray PVC jacket. Sequential footage marking.	Conductor	Bare Copper	<ul style="list-style-type: none"> • Security System • Intercom Systems • Sound/Audio System • Power-Limited Controls 	Pairs	Color
	Insulation	.010" (.25 mm) PVC		1	Black/Red - Red
	Jacket	PVC		2	Black/White - White
	NEC Articles	800 CMR		3	Black/Green - Green
	Voltage Rating	300 V		4	Black/Blue - Blue
Temp. Rating	75°C				

PART NO.	AWG/ PAIRS	STRAND	OUTER JKT THICKNESS		NOMINAL OD		AVAILABLE PUT-UPS	SHIP WT / 1M'
			INCH	mm	INCH	mm		
12221RSD	22/2 1 pr Shld/1 pr Unshld	7	.015	.38	.211	5.36	500'/1000'	18
12222RSD	22/2 Each Pair Shielded	7	.015	.38	.220	5.59	500'/1000'	21
12232RSD	22/3 Pair Overall Shield	7	.015	.38	.224	5.69	500'/1000'	26
12233RSD	22/3 Each Pair Shielded	7	.015	.38	.234	5.94	500'/1000'	33
122012RSD	22/3 2 pr Shld/1 pr Unshld	7	.015	.38	.179	4.55	500'/1000'	31
122014RSD	22/4 2 pr Shld/2 pr Unshld	7	.015	.38	.178	4.52	500'/1000'	34
120013RSD	20/3 2 pr Shld/1 pr Unshld	7	.015	.38	.199	5.05	500'/1000'	37
120014RSD	20/4 2 pr Shld/2 pr Unshld	7	.015	.38	.201	5.11	500'/1000'	46
11821RSD	18/2 1 pr Shld/1 pr Unshld	7	.015	.38	.262	6.65	500'/1000'	34
11822RSD	18/2 Each Pair Shielded	7	.015	.38	.281	7.14	500'/1000'	41
118232RSD	18/3 Overall Shield	7	.015	.38	.289	7.34	500'/1000'	52
11833RSD	18/3 Each Pair Shielded	7	.015	.38	.299	7.59	500'/1000'	55
118014RSD	18/4 2 pr Shld/2 pr Unshld	7	.015	.38	.219	5.56	500'/1000'	69