

Commercial Applications

CMP/FT6 Rated Shielded



RoHS Compliant

Cables are manufactured to meet current NEC guidelines and are verified by outside standards organizations including UL and ETL.

Product Description	Specifications	Applications	Color Code Chart				
Bare copper conductors, Low smoke PVC insulation, Shielded tape with drain wire, Natural low smoke PVC jacket with rip cord. Sequential footage marking.	Conductor	Bare Copper	<ul style="list-style-type: none"> • Security Systems • Intercom Systems • Sound/Audio System • Power-Limited Controls 	Cond	Color	Cond	Color
	Insulation	Low Smoke PVC		1	Black	11	Pink
	22 - 16 AWG	.009" PVC		2	Red	12	Tan
	14 - 12 AWG	.011" PVC		3	White		
	Jacket	Low Smoke PVC		4	Green		
	NEC Articles			5	Brown		
22 - 16 AWG	725/CL2P 800/CMP	6	Blue				
14 - 12 AWG	725 CL3P	7	Orange				
Voltage Rating		8	Yellow				
22 - 16 AWG	300 V	9	Purple				
14 - 12 AWG	150 V	10	Gray				
Temp. Rating	75°C						

PART NO.	AWG/ COND	STRAND	OUTER JKT THICKNESS		NOMINAL OD		AVAILABLE PUT-UPS	SHIP WT / 1M'
			INCH	mm	INCH	mm		
932202SD	22/2	SOL	.015	.38	.125	3.18	500'/1000'	13
912202SD	22/2	7	.015	.38	.132	3.35	500'/1000'	13
932204SD	22/4	SOL	.015	.38	.126	3.20	500'/1000'	20
912204SD	22/4	7	.015	.38	.150	3.81	500'/1000'	20
912206SD	22/6	7	.015	.38	.178	4.52	500'/1000'	26
912208SD	22/8	7	.015	.38	.193	4.90	500'/1000'	37
912210SD	22/10	7	.015	.38	.225	5.72	500'/1000'	46
912002SD	20/2	7	.015	.38	.145	3.68	500'/1000'	17
912004SD	20/4	7	.015	.38	.167	4.24	500'/1000'	27
911802SD	18/2	7	.015	.38	.162	4.11	500'/1000'	23
911803SD	18/3	7	.015	.38	.175	4.45	500'/1000'	30
911804SD	18/4	7	.015	.38	.191	4.85	500'/1000'	37
911806SD	18/6	7	.015	.38	.229	5.82	500'/1000'	56
911808SD	18/8	7	.015	.38	.259	6.58	500'/1000'	66
911809SD	18/9	7	.015	.38	.269	6.83	500'/1000'	73
911812SD	18/12	7	.018	.46	.309	7.85	500'/1000'	99
911602SD	16/2	19	.015	.38	.187	4.75	500'/1000'	33
911603SD	16/3	19	.015	.38	.198	5.03	500'/1000'	45
911604SD	16/4	19	.015	.38	.218	5.54	500'/1000'	59
911402SD	14/2	19	.015	.38	.229	5.82	500'/1000'	54
911403SD	14/3	19	.015	.38	.243	6.17	500'/1000'	70
911404SD	14/4	19	.015	.38	.264	6.71	500'/1000'	86
911202SD	12/2	19	.015	.38	.263	6.68	500'/1000'	68
911204SD	12/4	19	.015	.38	.303	7.70	500'/1000'	121